

Optional Features

- Ground Fault Interruptor Cord
- Open Gun - No Trigger Control
- Steam Combination
- Stainless Steel Coil Wrapper
- Electronic Ignition
- Total Stainless Steel Package
- Adjustable Thermostat
- Hour Meter
- Draft Diverter
- Time Delay Shutdown



**GAS-FIRED
HOT WATER
WASHER**

Every fixed location in plant cleaning system has its own unique set of extraordinary requirements. A powerfully simple solution to your most basic cleaning needs is found in a TUFF Stationary, Gas-Fired Hot Water Washer. As is every TUFF washer, you can count on strength and endurance. Plus our wide range of stationary hot water units has been designed with enough standard and optional versatility to satisfy your particular cleaning needs. Choose between two clean-burning environmentally safe fuels, natural gas or liquid propane, to fuel a high performance vertically mounted burner. Heavy duty, schedule 80 heating coil pipe means years of trouble free service.

The powerful pumping unit and controls are housed with the burner inside sheet metal shrouds to prevent unauthorized "maintenance". Optional "lock out" boxes are available to prevent access to the on/off switch and chemical control. Of course, operator and equipment safety are standard by design.

Standard Features

- Triplex Ceramic Plunger Pump with Brass Head
- Gas-Fired Burner with Standing Pilot Ignition Control
- "Super Tuff" Polyurethane Coated Steel Frame
- High Pressure Chemical with Metering Valve
- Schedule 80 Coil Pipe
- 50Ft. - 3000 PSI Working Pressure Delivery Hose
- Trigger Control: Trigger Gun & Unloader
- Safety Pressure Relief Valve
- High Temp Safety Limit Switch
- Low Water Safety Shutoff Valve
- Bypass Heat Relief/Pump Saver

General Specifications

Model(s)	Flow GPM	Pressure PSI	Motor HP	Motor Voltage	Amp Draw	BTU	Dimensions L x W x H	Weight Lbs.
2-1500 EHGVA	2.0	1500	2.0	115V	17	260,000	50 x 16 x 44	425
3-1100 EHGVA	2.8	1050	2.0	115V	17	340,000	50 x 16 x 44	425
3.5-1500 EHGVA	3.2	1500	3.0	208-230V	14-13	450,000	52 x 18 x 46	450
3-1600 EHGVA	2.8	1600	3.0	208-230V	14-13	260,000	50 x 16 x 44	425
3-2000 EHGVA	2.8	2000	4.0	208-230V	21-19	340,000	52 x 18 x 46	450
4-1500 EHGVA	4.1	1500	4.0	208-230V	21-19	540,000	54 x 20 x 49	475
4-2000 EHGVA	3.6	2000	5.0	208-230V	25-23	500,000	54 x 20 x 49	475
5-1500 EHGVA	4.9	1500	5.0	208-230V	25-23	550,000	58 x 24 x 52	500
4-2500 EHGVA	3.6	2500	6.0	208-230V	28-26	500,000	54 x 20 x 49	475
5-2000 EHGVA	4.9	2000	6.0	208-230V	28-26	550,000	58 x 24 x 52	500
4-3000 EHGVA	3.6	3000	7.5	208-230V	37-35	500,000	54 x 20 x 49	475
5-2500 EHGVA	4.9	2500	7.5	208-230V	37-35	550,000	58 x 24 x 52	500