



# "Vertical" Hot Water Pressure Washers

The vertical style achieves maximum heating efficiency with the burner positioned below the heating coil.

1000 – 3000 psi

**Super-Mobile**

26" X 36". That's all the floor space required to park the super-mobile dolly-style TUFF "Vertical" Hot Water Pressure Washer. The vertical style achieves maximum heating efficiency with the burner positioned below the heating coil. The insulated coil/combustion chamber assembly is mounted on a sturdy "Super Tuff" polyurethane coated tubular frame that allows easy access to all components. The float tank, constructed of long lasting stainless steel, provides constant inlet flow, while the large accessible fuel tank means hours of non-stop operation. Of course, TUFF chooses only the most powerful, longest lasting pumping components. The "Big Blast" cleaning power of the TUFF hot water is enhanced by the high pressure detergent application feature.

For years to come, a powerful, durable, and safe TUFF Vertical Hot Water Washer can make your hardest cleaning jobs quicker and easier.

#### Standard Features:

- Triplex Ceramic Plunger Pump with Brass Head
- Oil-Fired Burner with Automatic Ignition Control
- Stainless Steel Float Tank
- "Super Tuff" Polyurethane

#### Optional Features

- Ground Fault Interruptor Cord
- Open Gun - No Trigger Control
- Steam Combination
- Stainless Steel Package
- Adjustable Thermostat
- Hour Meter
- Three Phase Motors/Starters

#### General Specifications:

Model(s)	Flow GPM	Pressure PSI	Motor HP	Motor Voltage	Amp Draw	Fuel Gal.	Dimensions L x W x H	Weight Lbs.
2-1000 EHOVA	2.0	1000	1.5	115V	18	8.4	36X24X48	350
3-800 EHOVA	2.8	800	1.5	115V	18	8.4	36X24X48	350
2-1500 EHOVA	2.0	1500	2.0	115V	22	8.4	36X24X48	350
3-1100 EHOVA	2.8	1050	2.0	115V	22	8.4	36X24X48	350
3.5-1500 EHOVA	3.2	1500	3.0	208-230V	18-16	8.4	36X24X48	350
3-1600 EHOVA	2.8	1600	3.0	208-230V	18-16	8.4	36X24X48	350
3-2000 EHOVA	2.8	2000	4.0	208-230V	25-23	8.4	36X24X48	350
4-1500 EHOVA	4.1	1500	4.0	208-230V	25-23	8.4	36X24X48	350
4-2000 EHOVA	3.6	2000	5.0	208-230V	29-27	8.4	36X26X48	400
5-1500 EHOVA	4.9	1500	5.0	208-230V	29-27	8.4	36X26X48	400
4-2500 EHOVA	3.6	2500	6.0	208-230V	32-30	8.4	36X26X48	450
5-2000 EHOVA	4.9	2000	6.0	208-230V	32-30	8.4	36X26X48	450
4-3000 EHOVA	3.6	3000	7.5	208-230V	41-39	8.4	36X26X48	500
5-2500 EHOVA	4.9	2500	7.5	208-230V	41-39	8.4	36X26X48	500