

Armour Plate

Urethane-Fortified Floor Finish

Highly Durable, Easily Maintained, Easily removed, excellent heel mark resistance.

This product is designed for high-speed and low-speed floor machines. Its combination of acrylic resin fortified with durable urethane provides a long wearing film that responds readily to high speed burnishing as well as low speed polishing.

This product provides a clear film which will not discolor with aging and exhibits excellent mark and scuff resistance. It has outstanding detergent and water resistance but can be removed easily with an amine based stripper like our Free 'N' Easy norinse stripper.

This product is recommended for all resilient tile including asphalt, vinyl, vinyl composition, rubber, linoleum, terrazzo, and other masonry surfaces. It is ideally suited for heavy traffic areas such as supermarkets, shopping malls, restaurants, retail stores and office buildings.

Directions:

- 1. Remove all old wax and/or finish using an amine stripper. Pick up solution with a wet vacuum.
- Scrub rinse with clear water and allow floor to dry thoroughly.
- Apply this product with a rayon mop or gravity fed applicator.
- Allow to dry until "tack free" and apply a second coat. Apply a total of four coats for optimum protection and beauty.

Maintenance

- 1. Dust mop daily with mop treated with a water-based dust mop produt.
- Damp mop as required with a neutral cleaner.
- Burnish/Polish weekly, or more often if necessary, with a 1500 rpm machine and high speed burnishing pad.
- When required, a restorer product can be used to enhance the gloss.

COVERAGE: 2000 sq. ft./gal.

CAUTION:

Contains polymer emulsions. Undiluted product may cause eye irritation. Avoid contact with eyes. Do not take internally. FIRST AID: In case of contact, flush eyes with plenty of water for 15 minutes. If irritation persists, see a doctor.

KEEP OUT OF REACH OF CHILDREN KEEP FROM FREEZING

FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY